

# router

## Parameters

version - usage: router.version('1.0')

## Syntax for endpoint (METHOD) definition

```
router.METHOD('route/path/{variable}') {
  strategy(STRATEGY_NAME){
    ... strategy parameters ...
  }
  accessPermission 'groupName1', 'groupName2', '[roleName1]',
  '[roleName2]', ...
  mapJson 'notesFieldName', json:'jsonFieldName', type:
  'STRING|INTEGER|DOUBLE|DATETIME|ARRAY_OF_STRING|ARRAY_OF_INTEGER|ARRAY_OF_D
  OUBLE|ARRAY_OF_DATETIME', isformula: true/false, formula: '', readonly:
  true/false, writeonly: true/false
  mapJson ...
    events EVENT_NAME: {
    }
  }
}
```

METHOD - one of:

- GET
- POST
- DELETE

STRATEGY\_NAME - one of:

- DOCUMENT\_BY\_UNID
- DOCUMENT\_FROM\_VIEW\_BY\_KEY
- VIEWENTRIES\_PAGED
- VIEWENTRIES\_BY\_CATEGORY\_PAGED
- DOCUMENTS\_BY\_FORMULA\_PAGED
- DOCUMENTS\_BY\_SEARCH\_FT\_PAGED
- DOCUMENTS\_BY\_VIEW\_PAGED
- DOCUMENTS\_FROM\_VIEW\_BY\_KEY\_PAGED

accessPermission

mapJson