

router

Parameters

version - usage: router.version('1.0')

Syntax for endpoint (METHOD) definition

```
router.METHOD('route/path/{variable}') {
  strategy(STRATEGY_NAME){
    ... strategy parameters ...
  }
  accessPermission 'groupName1', 'groupName2', '[roleName1]', '[roleName2]', ...
  mapJson 'notesFieldName', json:'jsonFieldName', type:
'String|Integer|Double|Datetime|Array_of_String|Array_of_Integer|Array_of_Double|Array_of_Datetime', isformula:
true/false, formula: '', readonly: true/false, writeonly: true/false
  mapJson ...
    events EVENT_NAME: {
    }
  }
}
```

METHOD - one of:

- GET
- POST
- DELETE

STRATEGY_NAME - one of:

- DOCUMENT_BY_UNID
- DOCUMENT_FROM_VIEW_BY_KEY
- VIEWENTRIES_PAGED
- VIEWENTRIES_BY_CATEGORY_PAGED
- DOCUMENTS_BY_FORMULA_PAGED
- DOCUMENTS_BY_SEARCH_FT_PAGED
- DOCUMENTS_BY_VIEW_PAGED
- DOCUMENTS_FROM_VIEW_BY_KEY_PAGED

[accessPermission](#)

[mapJson](#)